

POLYCOAT - BT

POLYMER MODIFIED BITUMINOUS INSULATING COATING

POLYCOAT BT is a one component coating, specially developed to act as heat barrier. It forms a tough, resilient film upon drying. It is a ready to use coating which requires no thinning. Being water based it is safe to handle and use. It is ecofriendly.

APPLICATIONS

- Excellent adhesion to primed concrete surfaces, mortars, screeds and variety of other surfaces make **POLYCOAT BT** an ideal choice as sandwich membrane.

SALIENT FEATURES

- Easy to use, requires no thinning
- Economical heat barrier
- Flexible

INSTRUCTIONS FOR USE

Stir the contents well and then apply by trowel

SURFACE PREPARATION

To achieve maximum performance, it is extremely important that,

- Surface should be free from dust, oil, grease etc.
- Use sand blasting or high pressure water jet to get clean, dust free sound surface.

TECHNICAL DATA

Appearance	:	Brownish black viscous emulsion
Sp.Gravity @ R.T.	:	0.60
Coverage	:	Approx 2 sq m/kg (1000 micron DFT)

PACKING

20,200 Ltrs. In HDPE/MS containers.

STORAGE & SHELF LIFE

- It has a shelf life of 6 months when stored in original packing in a cool, dry place.

NOTE : The product has tendency to dry up, especially in low humidity regions. It may then be difficult to takeout material containers. In such situations, cut open the containers from top and add enough water under stirring so as to achieve a trowellable consistency.



DISCLAIMER

This information is accurate and reliable to the best of the knowledge. It is meant as a guideline only. Sunanda Speciality Coatings Pvt. Ltd. (SSCPL) cannot give any guarantees under any circumstances for the results, or assume any obligation or liability in connection with the use of this information. It is recommended that the product be tested to determine its suitability for specific applications. Since, SSCPL has no control over how others may use its products; it is recommended that the Specifier, Architect, Engineer, Contractor and Owner assume all the responsibilities in connection therewith.