



POLYTEXT FINISH

Acrylic Textured Exterior Coating

POLYTEXT FINISH is a ready to use, economical, acrylic polymer textured finish coating for beautifying and protecting concrete structures. It is a simple, decorative, aesthetic, and durable coating.

USES

- For exterior and interior applications on sand-faced, plastered, concrete or brick surfaces of housing societies, hospitals, commercial complexes, shopping malls etc.

ADVANTAGES

- Adheres strongly to new/ old hardened concrete surface and exterior paint.
- Hides plaster cracks, due to excellent flexibility & elasticity.
- Makes the surface water proof, resistant to fungal attack and carbonation.
- Acts as fire retardant.
- Breaths out trapped moisture.
- Frequent repainting is not required, low on maintenance..

PROPERTIES

Appearance: Light Beige/ Off- White paste

Drying time : Dry to touch : 30 minutes Dry to recoat : 12-16 hours

Finish coat : Depends on ambient conditions.

INSTRUCTIONS FOR USE

Surface Preparation & Cleaning

- Life and performance of POLYTEXT FINISH is directly dependent on the extent of cleaning.
- Clean the surface to remove dirt, loose particles, flaking paint, etc using brush and water jet.
- Examine the surface closely for any cracks or openings.
- Fill holes, dents and cracks, using mixture of white cement and fine sand in the ratio 1:3,

Mixing

- Open the container and stir the contents well with a stirrer to attain uniform consistency. If required add 5-10 % water by volume to get easily spread able consistency. Stir thoroughly.

Application

- Apply POLYTEXT FINISH using a flat trowel at a thickness of 2-3 mm.
- Repeat trowel on the spread material in one direction only till desired finish is obtained
- Remove excess POLYTEXT FINISH with a damp cloth before material sets.
- Cure for 12-16 hours minimum, prior to application of any exterior paint.
- During the entire application & set period, protect the coating from dust, dirt, water etc.

COVERAGE

0.2 – 0.3 M² per kg of POLYTEXT FINISH for an average thickness of 2mm. depending on roughness of surface, desired pattern and method of application.

PACKING

- Kg.

STORAGE SHELF LIFE

- 1 months when stored in a cool & dry place; Away from direct sunlight, in sealed packing.

NOTE: POLYTEXT FINISH must be top coated with desired shade of SUNEXT 8 or any acrylic emulsion exterior coating (refer to data sheet).

- If after application POLYTEXT FINISH is left as such for long time, then clean it with water before applying the top coat.

DISCLAIMER

This information is accurate and reliable to the best of the knowledge. It is meant as a guideline only. Sunanda Speciality Coatings Pvt. Ltd. (SSCPL) cannot give any guarantees under any circumstances for the results, or assume any obligation or liability in connection with the use of this information. It is recommended that the product be tested to determine its suitability for specific applications. Since, SSCPL has no control over how others may use its products; it is recommended that the Specifier, Architect, Engineer, Contractor and Owner assume all the responsibilities in connection therewith.