

## SUNEXT S

### SEMI-ACRYLIC EMULSION EXTERIOR COATING

**SUNEXT S** is a single component, economical semi-acrylic emulsion exterior coating. It protects exteriors from carbonation and extreme climatic conditions; provides long lasting and durable finish to external surfaces.

#### USES

- SUNEXT S is used as an anti-carbonation external surface coating.

#### ADVANTAGES

- Does not peel or crack. Good resistance to weathering.
- Resists formation of algae & fungus. No carbonation deposits, resulting in fresh look of the coating for years. Increases the total service life of the structure.
- U.V. Resistant. Washable to remove dirt and stains. Reduce maintenance cost.

#### PROPERTIES

Sp.Gravity @ R T	:	1.30 ± 0.05
pH	:	8 to 10
Volume solids	:	45 to 50 %

#### INSTRUCTIONS FOR USE

##### Surface Preparation & Cleaning

- Life and performance of SUNEXT S depends on the quality of cleaning.
- Clean the surface to remove dirt, loose particles, flaking paint, etc using brush and water jet.
- Scrub it down to original hard bare surface.
- Examine the surface closely for any cracks or openings.
- Fill the cracks with POLYFILL AR and for specialized cracks use POLYALK EP mortar. (Refer to data sheet)



## APPLICATION

- Open the container and stir the contents well with a mechanical stirrer to attain uniform consistency.
- Add 400 mL of potable water to one litre of SUNEXT S in a clean container.
- Stir thoroughly. Apply it as a primer coat by brush, roller or spray.
- Allow the primer coat to dry and set for 4-6 hours.
- Depending on the recommendations, subsequently, apply two or three coats SUNEXT S directly without addition of water, at an interval of 6 hours between each coat. (For ease of application if required, add little water but not more than 100 mL per Litre of SUNEXT S.)
- After the final coat, allow it to set for 24 hours
- During the entire application & set period, protect the coating from dust, dirt, water etc.

## COVERAGE

- 10-12 M<sup>2</sup> / Litre/ coat ( depending upon surface)

## PACKING

- 1,5, 20 Litre. Available in all shades off white, ivory and light shades are recommended.

## STORAGE & SHELF LIFE

- 12 months when stored in a cool & dry place; Away from direct sunlight, in original sealed packing.

### DISCLAIMER

This information is accurate and reliable to the best of the knowledge. It is meant as a guideline only. Sunanda Speciality Coatings Pvt. Ltd. (SSCPL) cannot give any guarantees under any circumstances for the results, or assume any obligation or liability in connection with the use of this information. It is recommended that the product be tested to determine its suitability for specific applications. Since, SSCPL has no control over how others may use its products; it is recommended that the Specifier, Architect, Engineer, Contractor and Owner assume all the responsibilities in connection therewith.