



SUNPOLY PUTTY PUTTY FOR STUCC

SUNPOLY PUTTY is a premium, high quality acrylic wall putty. It gives fine, smooth and excellent finish. It contains special ingredients which impart good bonding of finishing coats to surfaces.

SALIENT FEATURES

- Single pack system
- High workability
- Good leveling effect
- Improves the adhesion of finishing coats to substrate
- Good hiding power

DIRECTIONS FOR USE

- Surface should be free of dirt, oil grease, fungus, loose particles, laitance , paint film etc. If required use blast-cleaning or high pressure water-jet cleaning. Allow the surface to dry properly. Larger and deep cracks should be filled with Polyfill AR.
- Apply one coat of **SUNPOLY PUTTY** with putty blade or trowel. Allow it to dry for 4 to 6 hrs. Then apply second coat in a direction at right angles to first coat direction. Allow it to dry for 4 to 6 hrs. Then if required, using fine sandpaper scrub it.
- Now the surface is ready to receive any desired topcoats.

TECHNICAL DATA

- Colour : White
- pH : 8.0 to 10.5
- Sp.Gravity @RT : 1.3 ± 0.05
- Volume solids : 55%

PACKING

- 1,5,20 Kgs in HDPE /MS containers

STORAGE & SHELF LIFE

- It has a shelf life of 3 months when stored in original packing in a cool, dry place.

DISCLAIMER

This information is accurate and reliable to the best of the knowledge. It is meant as a guideline only. Sunanda Speciality Coatings Pvt. Ltd. (SSCPL) cannot give any guarantees under any circumstances for the results, or assume any obligation or liability in connection with the use of this information. It is recommended that the product be tested to determine its suitability for specific applications. Since, SSCPL has no control over how others may use its products; it is recommended that the Specifier, Architect, Engineer, Contractor and Owner assume all the responsibilities in connection therewith.