

SUNPLAST-FRA

FORM RELEASE AGENT

SUNPLAST-FRA is VOC compliant form release agent composed of blend of hydrocarbons and emulsifiers. When mixed with water it forms an emulsion which can be easily applied to any type of form. After evaporation of water a film is formed on the form which prevents bonding of concrete to the form. This results in quick release of form.

SALIENT FEATURES

- Can be used for wood, steel
- Non staining
- Eliminates defects, voids, buildup of concrete
- No rusting of form
- Economical and ease of application

DIRECTION FOR USE

- The form surface over which **SUNPLAST-FRA** is to be applied should be clean and free from remains of concrete and cement splashes.
- Dilute **SUNPLAST-FRA** with water in a ratio 1:30 (max), under stirring. Water is to be added to **SUNPLAST-FRA**. Continue stirring till a fine dispersion is obtained
- Apply emulsion by brush, spray or mopping with cotton rags. Allow about 30 min for absorption and film formation. After this concreting can be started.

TECHNICAL DATA

1. Appearance : Clear yellow coloured liquid
2. Sp.Gr.@30°C : 0.95 ± 0.05
3. Dilution ratio : Mix 1 part with maximum of 30 parts of water
4. Coverage : 50m/kg depending on surface

PACKING

1,5,20,200 Kgs. HDPE /MS containers

STORAGE AND SHELF LIFE

It has a shelf life of 12 months when stored in original packing in a cool dry place.

DISCLAIMER

This information is accurate and reliable to the best of the knowledge. It is meant as a guideline only. Sunanda Speciality Coatings Pvt. Ltd. (SSCPL) cannot give any guarantees under any circumstances for the results, or assume any obligation or liability in connection with the use of this information. It is recommended that the product be tested to determine its suitability for specific applications. Since, SSCPL has no control over how others may use its products; it is recommended that the Specifier, Architect, Engineer, Contractor and Owner assume all the responsibilities in connection therewith.