

POLYFILL AR

ELASTOMERIC ACRYLIC CRACK FILLER

POLYFILL AR is pure acrylic, polymer modified ready to use paste. It is specially formulated crack repair material with auto suction property.

USE

- Crack filler for plasters, IPS, cement sand screeds and non-structural cracks.

ADVANTAGES

- One pack easy to use, non-shrink, impermeable system.
- No bonding coat or curing is required.
- Excellent flexibility and good resistant to UV rays.
- Exceptionally good adhesion property.
- Sufficiently smooth finish, suitable for further painting application.

PROPERTIES

Plastic Density	:	1300 kg/m ³
Application thickness	:	Max. 15 mm
Final setting time at 30°C	:	12 hrs

INSTRUCTIONS FOR USE

- Do not open the cracks.
- Clean the cracks so as to free them from oil, dust, loose particles etc.
- Moisten the surface with water.
- Fill the crack with POLYFILL AR using spatula or a putty knife.
- While applying avoid formation of cavity or bubbles.
- After filling, allow the surface to dry for at least 24 hrs.
- Apply in layers at 24 hours interval, if the depth of the crack is more than 10 mm.

COVERAGE

- 25 RM per Kg for 8 mm thick and 6 mm depth crack.

PACKING

- 1, 5 Kg.

STORAGE & SHELF LIFE

- 6 months when stored in a cool & dry place; Away from direct sunlight, in original sealed packing.

DISCLAIMER

This information is accurate and reliable to the best of the knowledge. It is meant as a guideline only. Sunanda Speciality Coatings Pvt. Ltd. (SSCPL) cannot give any guarantees under any circumstances for the results, or assume any obligation or liability in connection with the use of this information. It is recommended that the product be tested to determine its suitability for specific applications. Since, SSCPL has no control over how others may use its products; it is recommended that the Specifier, Architect, Engineer, Contractor and Owner assume all the responsibilities in connection therewith.