

SUNQUASEAL

AQUA REACTIVE, POLYURETHANE BASED LEAKAGE SEALING LIQUID

SUNQUASEAL is a special insitu sealing liquid specially formulated to stop leakages from the joints of window frames and masonry surface. When it comes in contact with water, it forms a tough, resilient gel which is stable and does not crumble under pressure. It can penetrate easily into any crevice or crack and plug them effectively and permanently.

USES

- Stops leakages from joints of window frame and masonry surface.
- Stops leakages from small or large caliber pipe lines.

PROPERTIES

Appearance : Pale yellow coloured liquid
Viscosity@ 25° C : 1300 ± 400 cps
Sp.Gravity@ 25° C : 1.16± 0.05

INSTRUCTION FOR USE

- If the area where SUNQUASEAL is to be injected is already wet, then there is no need to specially wet it, otherwise wet using a water jet.
- Dry the other surrounding area completely.
- Inject SUNQUASEAL using a syringe directly between the gaps of window frame and window sills.
- For other applications like injection in damp concrete masses, contact our CMCD for design of injection system.

PRECAUTIONS

- Use gloves and safety goggles.
- Skin contact: Immediately wash thoroughly with soap and water.
- Inhalation: Remove to open air. Seek medical attention.
- Contact with eyes: Immediately wash under running water with eyelids open for at least 15 minutes. Seek medical attention.
- Ingestion: Seek medical attention. Do not induce vomiting
- Always work in well ventilated areas.



SUNANDA

SPECIALITY COATINGS PVT.LTD
AN ISO 9001:2008 COMPANY

- If worker feels drowsy, move him to a location with fresh air for sometime.
- After opening the container, keep it air tight.

PACKING

- 1, 4 Kg.

STORAGE AND SHELF LIFE

- 1 month when stored in a cool & dry place, away from direct sunlight, in original sealed packing, away from naked flame.



DISCLAIMER

This information is accurate and reliable to the best of the knowledge. It is meant as a guideline only. Sunanda Speciality Coatings Pvt. Ltd. (SSCPL) cannot give any guarantees under any circumstances for the results, or assume any obligation or liability in connection with the use of this information. It is recommended that the product be tested to determine its suitability for specific applications. Since, SSCPL has no control over how others may use its products, it is recommended that the Specifier, Architect, Engineer, Contractor and Owner assume all the responsibilities in connection therewith.