

POLYALK TG

CEMENTITIOUS TILE GROUT

DESCRIPTION

POLYALK TG is cementitious one component tile grout, containing polymers, UV stable pigments and additives. It has excellent adhesion for joint grouting of ceramic tiles, mosaics, marble and natural stones. It is available in different shades like white, pink, maroon, red, blue, black etc.

USES

- For filling joints of all types of tiles on floors, walls-interior & exterior, bathroom & toilet, and swimming pools etc.

ADVANTAGES

- Ready to use, add only water at site.
- Joints up to 6 mm width may be filled.
- Resistant to cracks.
- Excellent adhesion and impermeable to water.
- Good open time.
- Non shrink.
- Available in colour matching with tiles.

PROPERTIES

- Appearance : White or coloured free flowing Powder.
- Pot-life : 1:00 hour ± 15 minutes.
- Complete cure : 7 days approximately.

INSTRUCTION FOR USE

Surface Preparation

- Clean the grouting joint surface and make free from used tile adhesive material, loose particles, dust etc.
- Fill the joints 24 hours after fixing the tiles.

Mixing

- Mix 2 -2.5 parts POLYALK TG to 1 part of clean water by volume.
- Mix thoroughly to get lump free homogeneous paste.
- Allow the material to stand for 5 minutes, and again stir the mixture.

Application

- Spread the mixed paste into the joints with trowel and finish the surface.
- Remove surplus POLYALK TG with damp cloth.
- Clean the area after the filings have hardened

COVERAGE

- Coverage per kg of POLYALK TG is square feet

JOINT WIDTH	TILES SIZES					
	6" x 6"	6" x 12"	4" x 8"	8" x 8"	10" x 10"	12" x 12"
2 mm	94	130	88	130	158	184
4 mm	49	64	46	64	79	93
6 mm	32	42	30	43	55	62

Above coverage are for guidance only. Actual coverage should be established at site by selecting suitable area.

PACKING

- 1, 5, 25 Kg bags.

STORAGE AND SHELF LIFE

- 6 months when stored in a cool & dry place, away from direct sunlight, in original sealed packing.

DISCLAIMER

This information is accurate and reliable to the best of the knowledge. It is meant as a guideline only. Sunanda Speciality Coatings Pvt. Ltd. (SSCPL) cannot give any guarantees under any circumstances for the results, or assume any obligation or liability in connection with the use of this information. It is recommended that the product be tested to determine its suitability for specific applications. Since, SSCPL has no control over how others may use its products; it is recommended that the Specifier, Architect, Engineer, Contractor and Owner assume all the responsibilities in connection therewith.